

---

## Decorative Handle

### Installation Instructions Modern Series Doors

---

Detailed instructions for assembly of this handle on the Modern Series doors is covered with these instructions. The instruction manual that comes with your door shows the correct sections and height above the floor for mounting the two lift handles.



**WARNING**

**NEVER PLACE HANDS BETWEEN DOOR SECTIONS WHEN LIFTING DOOR TO AVOID INJURY**



Example of a horizontal handle mount to match the panel flow Reserve Modern Series.



Example of horizontal and vertical handle mount Canyon Ridge modern series.

## Outside and Inside Lift Handle Attachment For Modern Series Doors.

Use supplemental instructions that come with your door to determine general location of lower and upper handles as they position on the sections. The handles can be placed in both vertical and horizontal positions to fit the panel designs. See photo examples.

Once handle location is determined use inside galvanized handle as a template for marking location of holes to be drilled through door and overlay boards. Drill 5/16 holes straight through the door. (Fig. 8-A) Install bolts through inside handle (back of section) and thread mounting studs on the ends of each bolt by hand on the front side of the door. DO NOT tighten at this time.

**Note Bolt Length:** Outside handle will not install if bolt extends more than 5/8" beyond outside face of door.

**Canyon Ridge doors:** Use 2-3/4" long bolts on single overlay board locations. If your handle mount location has two overlay boards use the 3-1/2" long bolts.

**Modern Reserve doors:** Use 2-3/4" long bolts for Reserve Collection Modern wood doors. These doors are approximately 2-3/8" thick. The 3-1/2" long bolts are used on other door models and therefore can be discarded.

Assemble the outside lift handle with black screws provided. Orient set screw holes off to one side. (Fig.8B) Tighten black screws with 3/16 Hex or Allen wrench. (Not provided) Thread small set screws into handle until flush with outside of the handle.

Place outside lift handle over handle studs. (Fig. 8-C) Tighten set screws with 3/32" Hex or Allen wrench (Not provided) holding handle flush to door surface. At this point the long through bolts can be tightened one turn from the inside of the door section. Do not tighten excessively.

